



# Index

## IJQ6X

# 2011 A/C Catalogue

### Copper Tube

#### Copper Coil

- Coil as per ASTM B280 .....1
- Coil as per EN12735-1 .....1
- Coils as per ASTM B837 .....2

#### Copper Straight Tube

- Straight Tube as per ASTM B280, Hard Temper .....1
- Straight Tube as per EN12735-1, Hard Temper(R290), Half Hard Temper(R250) .....3

#### Copper Plumbing Tube

- Copper Plumbing Tube as per EN1057 .....4
- Copper Tubes for Plumbing, Drainage, Waste and Vent .....5

#### LWC

#### Copper Capillary Tube as per ASTM B360

#### Copper Fin Tube

- High Fin Tube .....6
- Boiling Tube .....7
- Straight Inner Grooved Copper Tube .....8
- Low Fin Tube .....8
- Cooling Tube .....8
- Spiral Tube .....8

### A/C Installation

#### Insulated Copper Tube

- Crosslinked PE Foam Insulated Copper Tube Single/Pair .....13
- Rubber Foam Insulated Copper Tube .....14
- Rubber Insulation .....15
- Rubber Insulation Tape .....16
- Crosslinked PE Foam Tape .....16
- Rubber Insulation Sheet .....17
- Insulation Material .....18
- Supports for Outdoor Unit .....19
- Screw Type Support SL/SP/SPS/SU/WB .....19
- Screw Type Support with Cross Bar HA/HB/HC/HD .....21
- Welded Type Support SRW/SSW/SIW/SZW .....22
- Ground Support GS1 .....23
- Roof Support RS .....24
- Condensation Collecting Tray CCT .....24
- PVC Floor Support .....25
- Accessories for Support .....25

### Installation Accessories

- PVC Rigid Drain Pipe .....27
- Drain Hose .....27
- Transparent Pipe .....27
- Embedded Pre-Installation Box .....28
- Covering Ducts for A/C Pipes .....29
- Metal Roof for Outdoor Units .....34
- Wooden Guard for Outdoor Units .....34
- Universal Remote Control .....35

### A/C Parts

- Copper Fitting .....37
- Copper Fitting .....37
- Brass Fitting .....49
- Vacuum Pump & Accessories Vacuum Pump & Accessories Recovery Unit, Station Leak Detector .....5
- Capacitor Run Capacitor Motor Start Capacitor Hard Start Capacitor Kits .....6
- Relay, Protector, Timer .....7
- Thermostat Defrost Type L Series Cooling only Type F2000/A2000 Danfoss Type K Series .....8
- Contactor One Pole Two Pole Three Pole .....67
- Filter Dryer Filter Dryer Core Filter .....69
- Manifold, Gauge and Testing Unit Manifold Charging Hose Testing Unit Quick Coupler Refrigerant Gauge .....74
- Can Charge Valve, Sight Glass Can Top Valve Piercing Valve Solder Union Charging Adapter Kit Sight Glass Split A/C Valve Hand Valve .....79
- Tool Tubing Tool Kit Flaring Tool Tube Bender Tube Cutter Tool Accessories Latches & Hinge .....83
- Silver Solder & Flux .....91
- Brazed Plate Heat Exchanger .....92

### Compressor

- Refrigerator Compressor .....93
- Air Conditioning Compressor .....93





www.sino-hvac.com  
 hvac@sinochem-nb.com  
 Tel. 86 574 87348868  
 Fax. 86 574 87364863

Copper Tube  
 AC installation  
 AC Parts  
 Compressor



2011 A/C Catalogue

## Copper Coil

### Refrigeration Tubes as per ASTM B280, in Coils, Soft Temper



ENDS CAPPED, IN SHRINKING WRAPPED BAG IN  
 CARDBOARD BOX

Outside Diameter		Wall Thickness (inch/mm)					Nominal Weight (kgs)		Packing	
(inch)	(mm)	0.030 0.76	0.032 0.81	0.035 0.89	0.045 1.14	0.050 1.27	(15 Meters)	(15.24 Meters)	Carton Dimension(cm <sup>3</sup> )	Coils per Carton
3/16	4.76						1.28	1.30	38x38x16	15
1/4	6.35						1.78	1.81	38x38x15	10
5/16	7.94						2.43	2.46	38x38x16	10
3/8	9.52						2.96	3.01	38x38x20	10
1/2	12.70						4.04	4.11	52x52x15	5
5/8	15.88						5.60	5.69	52x52x16	5
3/4	19.05						6.79	6.90	66x66x13.5	3
7/8	22.22						10.09	10.25	66x66x13.5	3
1-1/8	28.58						14.57	14.80	74x74x13.5	2

### Refrigeration Tubes As Per En12735-1, In Coils, Soft Temper (R220)

ENDS CAPPED, IN SHRINKING WRAPPED BAG IN CARDBOARD BOX

Outside Diameter		Wall Thickness	Nominal Weight (kgs)		Packing	
(inch)	(mm)	(mm)	(15 Meters)	(15.24 Meters)	Carton Dimension(cm <sup>3</sup> )	Coils per Carton
3/16	4.76	0.8	1.33	1.35	38x38x16	15
1/4	6.35	0.8	1.86	1.89	38x38x15	10
1/4	6.35	1.0	2.25	2.28	38x38x15	10
5/16	7.94	0.8	2.40	2.44	38x38x16	10
5/16	7.94	1.0	2.91	2.96	38x38x16	10
3/8	9.52	0.8	2.93	2.98	38x38x20	10
3/8	9.52	1.0	3.58	3.64	38x38x20	10
1/2	12.70	0.8	4.00	4.06	52x52x15	5
1/2	12.70	1.0	4.91	4.99	52x52x15	5
5/8	15.88	1.0	6.25	6.35	52x52x16	3
3/4	19.05	1.0	7.58	7.70	66x66x13.5	3
7/8	22.22	1.0	8.91	9.06	66x66x13.5	2
	8	0.8	2.42	2.46		
	8	1.0	2.94	2.99		
	10	0.8	3.09	3.14		
	10	1.0	3.78	3.84		
	12	1.0	4.62	4.69		
	15	1.0	5.88	5.97		
	18	1.0	7.14	7.25		
	22	1.0	8.82	8.96		





## Natural Gas and LPG as per ASTM B837, in Coils, Soft Temper.

ENDS CAPPED, IN SHRINKING WRAPPED BAG IN CARDBOARD BOX

Outside Diameter		Wall Thickness		Nominal Weight (kgs)		Packing	
(inch)	(mm)	(inch)	(mm)	(60 FT)	(18 Meters)	Carton Dimension(cm <sup>3</sup> )	Coils per Carton
3/8	9.52	0.030	0.76	3.41	3.36	45 x 45 x 18.5	8
1/2	12.70	0.035	0.89	5.38	5.30	50 x 50 x 18.5	6
5/8	15.88	0.040	1.02	7.76	7.64	55 x 55 x 18.5	5
3/4	19.05	0.042	1.07	9.85	9.70	60 x 60 x 18.5	4
7/8	22.22	0.045	1.14	12.31	12.11	65 x 65 x 18.5	3

## Copper Straight Tube

### Refrigeration Tubes as per ASTM B280, Straight Lengths, Hard Temper

ENDS CAPPED, WOODEN BOX PACKING



Outside Diameter		Wall Thickness		Nominal Weight (kgs)	
(inch)	(mm)	(inch)	(mm)	(5.8 Meters)	(6 Meters)
3/8	9.52	0.030	0.76	1.08	1.12
1/2	12.70	0.035	0.89	1.71	1.77
5/8	15.88	0.040	1.02	2.46	2.55
3/4	19.05	0.042	1.07	3.12	3.23
7/8	22.22	0.045	1.14	3.90	4.04
1-1/8	28.58	0.050	1.27	5.63	5.83
1-3/8	34.93	0.055	1.40	7.62	7.88
1-5/8	41.28	0.060	1.52	9.81	10.15
2-1/8	53.98	0.070	1.78	15.09	15.61
2-5/8	66.67	0.080	2.03	21.31	22.05
3-1/8	79.38	0.090	2.29	28.67	29.66
3-5/8	92.08	0.100	2.54	36.93	38.21
4-1/8	105	0.110	2.79	46.31	47.91

#### Imperial Standard Wire Gauges (SWG)

SWG Number	inch	mm
16	0.064	1.63
17	0.056	1.42
18	0.048	1.22
19	0.040	1.02
20	0.036	0.91
21	0.032	0.81
22	0.028	0.71
23	0.024	0.61
24	0.022	0.56
25	0.020	0.51
26	0.018	0.46
27	0.016	0.41





## Refrigeration Tubes as per EN 12735-1, Straight Lengths, Hard Temper(R290), Half Hard Temper (R250)



ENDS CAPPED, WOODEN BOX PACKING

Outside Diameter		Wall Thickness (mm)	Nominal Weight (kgs)	
(inch)	(mm)		(5.8 Meters)	(6 Meters)
1/2	12.7	1	1.90	1.97
5/8	15.88	1	2.42	2.50
3/4	19.05	1.25	3.61	3.74
7/8	22.22	1.25	4.26	4.40
1	25.40	1	3.96	4.10
1 1/8	28.58	1	4.48	4.63
1 1/8	28.58	1.25	5.55	5.74
1 3/8	34.92	1.25	6.84	7.07
1 5/8	41.27	1.25	8.12	8.40
2 1/8	53.97	1.25	10.70	11.07
2 1/8	53.97	1.65	14.02	14.50
2 5/8	66.67	1.25	13.28	13.74
2 5/8	66.67	1.65	17.42	18.02
2 5/8	66.67	2	21.00	21.73
3 1/8	79.37	1.65	20.83	21.54
3 1/8	79.37	2.5	31.21	32.29
3 1/2	88.90	2	28.23	29.20
3 5/8	92.07	1.65	24.23	21.07
3 5/8	92.07	2.5	36.37	37.62
4 1/8	104.80	1.65	27.63	28.59
4 1/8	104.80	2.5	41.53	42.96
	6	0.8	0.68	0.70
	8	0.8	0.94	0.97
	10	0.8	1.20	1.24
	10	1	1.46	1.51
	12	1	1.79	1.85
	15	1	2.27	2.35
	18	1	2.76	2.86
	22	1	3.41	3.53
	28	1.5	6.46	6.68
	35	1.5	8.16	8.44
	42	1.5	9.87	10.21
	54	2	16.89	17.47
	64	2	20.14	20.83
	76.10	2	24.07	24.90
	108	2.5	42.83	44.31





## Copper Plumbing Tube

### Copper Tubes for Plumbing as per EN1057

#### SPECIFICATIONS

Phosphorus Deoxidised, copper tubes alloy CW024A, or Cu-DHP

Temper: soft temper R-220, half-hard temper R-250, hard temper R-290

Nominal outside diameter	Nominal wall thicknesses												
	O.D.	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.5	2.0	2.5	3.0
6			•		•		•						
8		•••		•••		•••							
10			•										
12				•		•							
14													
15			•	•			•						
16							•						
18													
22						•	•		•	•			
25													
28						•			•	•			
35									•	•			
40													
42									•	•			
54									•	•	•		
64											•		
66,7									•				
70													
76,1										•	•		
80													
88,9											•		
108										•		•	
133										•			••
159											•		•••
219													•••
267													

• indicates the European recommended dimensions





## Copper Tubes For Plumbing, Drainage, Waste And Vent

### SPECIFICATIONS

Phosphorus Deoxidised, copper tubes alloy C12200

K, L, M according to ASTM B-88

Temper: Hard in straight lengths, up to 20FT

Soft in pancake, coils up to 100FT, DWV according to B-306

	Standard Size	Outside Diameter	Wall Thickness	Max. pressure Permitted	Theoretical Weight	
	inch	inch (mm)	inch (mm)	Lbs/Sq. Inch	Lb/Ft	(kg/m)
<b>K</b>	1/4	0.375 (9.52)	0.035 (0.89)	1,210	0.145	(0.215)
	3/8	0.500 (12.70)	0.049 (1.24)	1,266	0.269	(0.398)
	1/2	0.625 (15.88)	0.049 (1.24)	955	0.344	(0.508)
	5/8	0.750 (19.05)	0.049 (1.24)	824	0.418	(0.618)
	3/4	0.875 (22.22)	0.065 (1.65)	938	0.641	(0.951)
	1	1.125 (28.58)	0.065 (1.65)	725	0.839	(1.244)
	1-1/4	1.375 (34.93)	0.065 (1.65)	583	1.040	(1.538)
	1-1/2	1.625 (41.28)	0.072 (1.83)	540	1.360	(2.021)
	2	2.125 (53.98)	0.083 (2.11)	483	2.060	(3.064)
	2-1/2	2.625 (66.68)	0.095 (2.41)	441	2.930	(4.337)
<b>L</b>	3	3.125 (79.38)	0.109 (2.77)	427	4.000	(5.941)
	3-1/2	3.625 (92.08)	0.120 (3.05)	407	5.120	(7.603)
	4	4.125 (105.0)	0.134 (3.40)	399	6.510	(9.651)
	1/4	0.375 (9.52)	0.030 (0.76)	1,010	0.126	(0.187)
	3/8	0.500 (12.70)	0.035 (0.89)	882	0.198	(0.294)
	1/2	0.625 (15.88)	0.040 (1.02)	810	0.285	(0.424)
	5/8	0.750 (19.05)	0.042 (1.07)	701	0.362	(0.539)
	3/4	0.875 (22.22)	0.045 (1.14)	640	0.455	(0.673)
	1	1.125 (28.58)	0.050 (1.27)	555	0.655	(0.971)
	1-1/4	1.375 (34.93)	0.055 (1.40)	498	0.884	(1.314)
<b>M</b>	1-1/2	1.625 (41.28)	0.060 (1.52)	455	1.140	(1.692)
	2	2.125 (53.98)	0.070 (1.78)	398	1.750	(2.602)
	2-1/2	2.625 (66.68)	0.080 (2.03)	370	2.480	(3.675)
	3	3.125 (79.38)	0.090 (2.29)	355	3.330	(4.943)
	3-1/2	3.625 (92.08)	0.100 (2.54)	337	4.290	(6.368)
	4	4.125 (105)	0.110 (2.79)	326	5.380	(7.967)
	3/8	0.500 (12.70)	0.025 (0.64)	626	0.145	(0.216)
	1/2	0.625 (15.88)	0.028 (0.71)	555	0.204	(0.302)
	3/4	0.875 (22.22)	0.032 (0.81)	441	0.328	(0.486)
	1	1.125 (28.58)	0.035 (0.89)	384	0.465	(0.690)
1-1/4	1.375 (34.93)	0.042 (1.07)	370	0.682	(1.014)	
1-1/2	1.625 (41.28)	0.049 (1.24)	370	0.940	(1.390)	
2	2.125 (53.98)	0.058 (1.47)	327	1.460	(2.161)	
2-1/2	2.625 (66.68)	0.065 (1.65)	299	2.030	(3.004)	
3	3.125 (79.38)	0.072 (1.83)	284	2.680	(3.974)	
3-1/2	3.625 (92.08)	0.083 (2.11)	279	3.580	(5.315)	
4	4.125 (105)	0.095 (2.41)		4.660	(6.908)	





www.sino-hvac.com  
 hvac@sinochem-nb.com  
 Tel. 86 574 87348868  
 Fax. 86 574 87364863

Copper Tube  
 AC installation  
 AC Parts  
 Compressor



2011 A/C Catalogue

	Standard Size inch	Outside Diameter inch (mm)	Wall Thickness inch (mm)	Max. pressure Permitted Lbs/Sq. Inch	Theoretical Weight	
					lb/ft	(kg/m)
<b>DWV</b>	1-1/4	1.375 (34.93)	0.040 (1.02)	-	0.650	(0.968)
	1-1/2	1.625 (41.28)	0.042 (1.07)	-	0.809	(1.205)
	2	2.125 (53.98)	0.042 (1.07)	-	1.070	(1.585)
	3	3.125 (79.38)	0.045 (1.14)	-	1.690	(2.497)
	4	4.125 (105.0)	0.058 (1.47)	-	2.870	(4.270)

## LWC

### Copper Tubes On Level Wound Coils



Average O.D	Outside Diameter			Wall Thickness							
	0.30	0.35	0.41	0.5	0.6	0.7	0.75	0.8	0.9	1.0	1.2
3/16"	●	●	●	●	●	●	●	●	●	●	-
1/4"	●	●	●	●	●	●	●	●	●	●	●
5/16"	-	●	●	●	●	●	●	●	●	●	●
3/8"	-	●	●	●	●	●	●	●	●	●	●
1/2"	-	-	●	●	●	●	●	●	●	●	●
5/8"	-	-	-	-	●	●	●	●	●	●	●
3/4"	-	-	-	-	●	●	●	●	●	●	●

Note: Other sizes can be made as per customer's request according to mutual agreement.





## Copper Capillary Tube

### Air Conditioning And Refrigeration, Capillary Tubes as per ASTM B360



Material            Cu Alloy 12200  
 Packaging          Straight length in wooden boxes,  
                          Coils in carton boxes  
 Specification      According to individual customer specifications


Outside Diameter inch (mm)	Inside Diameter inch (mm)	Mean Wall Thickness inch (mm)	Weight Lb/ft (Kg/m)
0.072 (1.830)	0.026 (0.660)	0.023 (0.584)	0.01373 (0.0204)
0.072 (1.830)	0.028 (0.711)	0.022 (0.558)	0.01340 (0.0199)
0.081 (2.060)	0.031 (0.787)	0.025 (0.635)	0.01705 (0.0254)
0.081 (2.060)	0.033 (0.838)	0.024 (0.606)	0.01666 (0.0248)
0.087 (2.210)	0.036 (0.914)	0.0255 (0.648)	0.01910 (0.0284)
0.087 (2.210)	0.039 (0.991)	0.024 (0.606)	0.01842 (0.0239)
0.093 (2.360)	0.042 (1.070)	0.0255 (0.648)	0.02096 (0.0312)
0.097 (2.470)	0.046 (1.170)	0.025 (0.648)	0.02221 (0.0331)
0.099 (2.510)	0.049 (1.240)	0.025 (0.635)	0.02253 (0.0335)
0.106 (2.690)	0.054 (1.370)	0.026 (0.660)	0.02533 (0.0377)
0.112 (2.840)	0.059 (1.500)	0.0265 (0.673)	0.02760 (0.0411)
0.125 (3.180)	0.064 (1.630)	0.0305 (0.775)	0.03511 (0.0522)
0.125 (3.180)	0.070 (1.780)	0.0275 (0.698)	0.03266 (0.0486)
0.125 (3.180)	0.075 (1.910)	0.025 (0.635)	0.03054 (0.0454)
0.145 (3.680)	0.080 (2.030)	0.0325 (0.826)	0.04453 (0.0663)
0.145 (3.680)	0.085 (2.160)	0.030 (0.762)	0.04202 (0.0625)
0.145 (3.680)	0.090 (2.290)	0.0275 (0.698)	0.03936 (0.0586)
0.160 (4.060)	0.100 (2.540)	0.030 (0.762)	0.04750 (0.0707)
0.160 (4.060)	0.110 (2.790)	0.025 (0.635)	0.04111 (0.0611)
0.188 (4.780)	0.120 (3.030)	0.034 (0.864)	0.06377 (0.0949)
0.188 (4.780)	0.130 (3.300)	0.029 (0.737)	0.05616 (0.0836)
0.200 (5.080)	0.145 (3.680)	0.0275 (0.698)	0.05779 (0.0860)
0.220 (5.590)	0.160 (4.060)	0.030 (0.762)	0.06943 (0.103)
0.240 (6.100)	0.175 (4.450)	0.0325 (0.826)	0.08107 (0.121)







## Copper Fin Tube



### High Fin Tube

**Specification:**

This tube is an integral extended surface tube designed primarily for applications which require high outside-to-inside surface area ratios, such as direct fired water heaters, boilers, and applications for heating or cooling gases.

Packed in wooden boxes.

Nominal Inside Diameter inch (mm)	Actual Inside Diameter inch (mm)	Minimum Wall Under Fin inch (mm)	Maximum Fin Diameter inch (mm)	Minimum Fin Height inch (mm)	Weight Per Unit Length (kg/m)
<b>Dimensional Date -- 5 Fins Per Inch</b>					
1/2 (12.70)	0.506 (12.85)	0.061 (1.549)	1.438 (36.53)	0.350 (8.890)	1.469
7/8 (22.22)	0.881 (22.38)	0.061 (1.549)	1.854 (47.09)	0.375 (9.525)	2.568
1 (25.40)	1.007 (25.58)	0.061 (1.549)	1.938 (49.23)	0.350 (8.890)	2.928
<b>Dimensional Date -- 7 Fins Per Inch</b>					
5/8 (15.88)	0.631 (16.03)	0.039 (0.991)	1.562 (39.67)	0.375 (9.525)	1.800
3/4 (19.05)	0.756 (19.20)	0.055 (1.397)	1.688 (42.88)	0.350 (8.890)	2.126
7/8 (22.22)	0.881 (22.38)	0.046 (1.168)	1.859 (47.22)	0.375 (9.525)	1.934
<b>Dimensional Date -- 8 Fins Per Inch</b>					
5/8 (15.88)	0.631 (16.03)	0.061 (1.549)	1.250 (31.75)	0.210 (5.334)	1.988
7/8 (22.22)	0.881 (22.38)	0.046 (1.168)	1.857 (47.17)	0.375 (9.525)	2.643
7/8 (22.22)	0.881 (22.38)	0.061 (1.549)	1.857 (47.17)	0.375 (9.525)	3.348
<b>Dimensional Date -- 9 Fins Per Inch</b>					
1/2 (12.70)	0.506 (12.85)	0.061 (1.549)	1.438 (36.53)	0.350 (8.890)	1.875
5/8 (15.88)	0.631 (16.03)	0.039 (0.991)	1.562 (39.67)	0.375 (9.525)	1.943
5/8 (15.88)	0.631 (16.03)	0.061 (1.549)	1.562 (39.67)	0.350 (8.890)	2.202





### Boiling Tube

**Specification:**


This tube has unique fin form. Fins are inter-connected via specially designed duct under the fin. Snch design is helpful for continuous overflow of bubbles when the refrigerant boils. The fin has different form when machine unit has different heat flux.

It is suitable for water chilling machine unit with full fluid.

Packed in wooden boxes.

Standard Sizes		Plain End Dimensions		Finned Section Dimensions			
Outside Diameter inch (mm)	Nominal Wall inch (mm)	Outside Diameter inch (mm)	Nominal Wall inch (mm)	Fin Height inch (mm)	Min wall Under Fins inch (mm)	Number of fin	Inner Fin Height (mm)
<b>Dimensional Date -- 19 Fins Per Inch</b>							
5/8 (15.88)	0.035 (0.889)	0.623 (15.82)	0.052 (1.32)	0.063 (1.588)	0.031 (0.787)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.743 (18.87)	0.049 (1.24)	0.063 (1.588)	0.025 (0.635)	36	0.40
1 (25.4)	0.049 (1.254)	0.998 (25.35)	0.065(1.65)	0.063 (1.588)	0.044 (1.118)	38	0.40
<b>Dimensional Date -- 26 Fins Per Inch</b>							
5/8 (15.88)	0.035 (0.889)	0.623 (15.82)	0.052 (1.32)	0.063 (1.588)	0.031 (0.787)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.743 (18.87)	0.049 (1.24)	0.063 (1.588)	0.025 (0.635)	36	0.40
1 (25.4)	0.049 (1.254)	0.998 (25.35)	0.065(1.65)	0.063 (1.588)	0.044 (1.118)	38	0.40
<b>Dimensional Date -- 35 Fins Per Inch</b>							
3/4 (19.05)	0.028 (0.711)	0.748 (19.00)	0.043 (1.09)	0.038 (0.953)	0.023 (0.584)	36	0.40
3/4 (19.05)	0.035 (0.889)	0.748 (19.00)	0.050 (1.27)	0.038 (0.953)	0.030 (0.762)	36	0.40
3/4 (19.05)	0.042 (1.067)	0.748 (19.00)	0.058 (1.47)	0.038 (0.953)	0.037 (0.940)	36	0.40
<b>Dimensional Date -- 42Fins Per Inch</b>							
5/8 (15.88)	0.025 (0.635)	0.623 (15.82)	0.047 (1.19)	0.056 (1.422)	0.022 (0.559)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.748 (19.00)	0.043 (1.09)	0.034 (0.864)	0.025 (0.635)	36	0.40
1 (25.4)	0.049 (1.254)	0.998 (25.35)	0.058 (1.47)	0.034 (0.864)	0.037 (0.935)	38	0.40
<b>Dimensional Date -- 50Fins Per Inch</b>							
5/8 (15.88)	0.025 (0.635)	0.623 (15.82)	0.047 (1.19)	0.056 (1.422)	0.022 (0.559)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.748 (19.00)	0.043 (1.09)	0.034 (0.864)	0.025 (0.635)	36	0.40
1 (25.4)	0.042 (1.254)	0.998 (25.35)	0.058 (1.47)	0.034 (0.864)	0.037 (0.935)	38	0.40






### Straight Inner Grooved Copper Tubes

**Specification:**

The continuous or discontinuous spiral groove on inner surface of copper tube can increase contact area, change the flow type of refrigerant in the tube. The outer surface of copper tube can also be processed with corrugate spiral groove to expand range of use. It is suitable for heat exchanger in home air conditioner or dry evaporator in central conditioner.

Packed in wooden boxes.

O.D in (mm)	BWT (mm)	Number of fins	FIN HEIGHT (mm)	Helix Angle	Weight (kg/m)
(7.0)	0.330	60	0.203	12	0.0781
5/16 (7.94)	0.305	60	0.203	18	0.0804
3/8 (9.52)	0.305	60	0.203	18	0.0967
3/8 (9.52)	0.330	60	0.203	18	0.0989
3/8 (9.52)	0.356	60	0.203	18	0.1027
3/8 (9.52)	0.381	60	0.203	18	0.1205
3/8 (9.52)	0.406	60	0.203	18	0.1176
1/2 (12.7)	0.381	60	0.254	18	0.1622
1/2 (12.7)	0.406	60	0.254	18	0.1711
1/2 (12.7)	0.432	60	0.254	18	0.1792
1/2 (12.7)	0.456	60	0.254	18	0.1887
1/2 (12.7)	0.483	60	0.254	18	0.2064
5/8 (15.88)	0.498	75	0.305	23	0.2695
5/8 (15.88)	0.510	75	0.305	23	0.2695
5/8 (15.88)	0.510	75	0.305	25	0.3049
5/8 (15.88)	0.584	75	0.305	25	0.3240
5/8 (15.88)	0.635	60	0.305	27	0.3503
5/8 (15.88)	0.715	60	0.305	27	0.3726



### Low Fin Tube

**Specification:**

The outer surface of copper tube has continuous spiral fin.

It is suitable for lithium bromide machine unit or heat exchanger.

Packed in wooden boxes.

Standard Sizes		Plain End Dimensions		Finned Section Dimensions			
Outside Diameter inch (mm)	Nominal Wall inch (mm)	Outside Diameter inch (mm)	Nominal Wall inch (mm)	Fin Height inch (mm)	Min wall Under Fins inch (mm)	Number of fin	Inner Fin Height (mm)
<b>Dimensional Date -- 19 Fins Per Inch</b>							
5/8 (15.88)	0.035 (0.889)	0.623 (15.82)	0.052 (1.32)	0.063 (1.588)	0.031 (0.787)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.743 (18.87)	0.049 (1.24)	0.063 (1.588)	0.025 (0.635)	36	0.40
1 (25.4)	0.049 (1.254)	0.998 (25.35)	0.065 (1.65)	0.063 (1.588)	0.044 (1.118)	38	0.40
<b>Dimensional Date -- 26 Fins Per Inch</b>							
5/8 (15.88)	0.035 (0.889)	0.623 (15.82)	0.052 (1.32)	0.063 (1.588)	0.031 (0.787)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.743 (18.87)	0.049 (1.24)	0.063 (1.588)	0.025 (0.635)	36	0.40
1 (25.4)	0.049 (1.254)	0.998 (25.35)	0.065 (1.65)	0.063 (1.588)	0.044 (1.118)	38	0.40
<b>Dimensional Date -- 35 Fins Per Inch</b>							
3/4 (19.05)	0.028 (0.711)	0.748 (19.00)	0.043 (1.09)	0.038 (0.953)	0.023 (0.584)	36	0.40
3/4 (19.05)	0.035 (0.889)	0.748 (19.00)	0.050 (1.27)	0.038 (0.953)	0.030 (0.762)	36	0.40
3/4 (19.05)	0.042 (1.067)	0.748 (19.00)	0.058 (1.47)	0.038 (0.953)	0.037 (0.940)	36	0.40
<b>Dimensional Date -- 42Fins Per Inch</b>							
5/8 (15.88)	0.025 (0.635)	0.623 (15.82)	0.047 (1.19)	0.056 (1.422)	0.022 (0.559)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.748 (19.00)	0.043 (1.09)	0.034 (0.864)	0.025 (0.635)	36	0.40
1 (25.4)	0.049 (1.254)	0.998 (25.35)	0.058 (1.47)	0.034 (0.864)	0.037 (0.935)	38	0.40
<b>Dimensional Date -- 50Fins Per Inch</b>							
5/8 (15.88)	0.025 (0.635)	0.623 (15.82)	0.047 (1.19)	0.056 (1.422)	0.022 (0.559)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.748 (19.00)	0.043 (1.09)	0.034 (0.864)	0.025 (0.635)	36	0.40
1 (25.4)	0.042 (1.254)	0.998 (25.35)	0.058 (1.47)	0.034 (0.864)	0.037 (0.935)	38	0.40



www.sino-hvac.com  
 hvac@sinochem-nb.com  
 Tel. 86 574 87348868  
 Fax. 86 574 87364863

Copper Tube  
 AC installation  
 AC Parts  
 Compressor



2011 A/C Catalogue



### Cooling Tube

**Specification:**

The sharp boss in radial and axial directions on fin end of the tube can separate refrigerating drops and reduce their surface tension to make them drop faster. It has strong condensation effect. It is suitable for shell & tube heat exchanger.

Packed in wooden boxes.

Standard Sizes		Plain End Dimensions		Finned Section Dimensions			
Outside Diameter inch (mm)	Nominal Wall inch (mm)	Outside Diameter inch (mm)	Nominal Wall inch (mm)	Fin Height inch (mm)	Min wall Under Fins inch (mm)	Number of fin	Inner Fin Height (mm)
<b>Dimensional Date -- 19 Fins Per Inch</b>							
5/8 (15.88)	0.035 (0.889)	0.052 (15.82)	0.052 (1.32)	0.063 (1.588)	0.031 (0.787)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.049 (18.87)	0.049 (1.24)	0.063 (1.588)	0.025 (0.635)	36	0.40
1 (25.4)	0.049 (1.254)	0.065 (25.35)	0.065 (1.65)	0.063 (1.588)	0.044 (1.118)	38	
<b>Dimensional Date -- 26 Fins Per Inch</b>							
5/8 (15.88)	0.035 (0.889)	0.052 (15.82)	0.052 (1.32)	0.063 (1.588)	0.031 (0.787)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.049 (18.87)	0.049 (1.24)	0.063 (1.588)	0.025 (0.635)	36	0.40
1 (25.4)	0.049 (1.254)	0.065 (25.35)	0.065 (1.65)	0.063 (1.588)	0.044 (1.118)	38	
<b>Dimensional Date -- 35 Fins Per Inch</b>							
3/4 (19.05)	0.028 (0.711)	0.748 (19.00)	0.043 (1.09)	0.038 (0.953)	0.023 (0.584)	36	0.40
3/4 (19.05)	0.035 (0.889)	0.748 (19.00)	0.050 (1.27)	0.038 (0.953)	0.030 (0.762)	36	0.40
3/4 (19.05)	0.042 (1.067)	0.748 (19.00)	0.058 (1.47)	0.038 (0.953)	0.037 (0.940)	36	0.40
<b>Dimensional Date -- 42 Fins Per Inch</b>							
5/8 (15.88)	0.025 (0.635)	0.623 (15.82)	0.049 (1.19)	0.056 (1.422)	0.022 (0.559)	34	0.40
3/4 (19.05)	0.028 (0.711)	0.748 (19.00)	0.043 (1.09)	0.034 (0.864)	0.025 (0.635)	36	0.40
1 (25.4)	0.049 (1.254)	0.998 (25.35)	0.058 (1.47)	0.034 (0.864)	0.037 (0.935)	38	0.40

### Spiral Tube

**Specification:**

The copper tube is twisted to form with spiral groove on outer surface. Since there is cavity in the cross-section of spiral groove, such tube can be twisted randomly and be installed in narrow space. It is suitable for double pipes heat exchanger in machine unit.

Packed in wooden boxes.



Outside Diameter Inch (mm)	Tolerances Of Wall Thickness(± mm)									
Average O.D	0.35	0.41	0.5	0.6	0.7	0.75	0.8	1.0	1.2	
1/2 (12.7)		0.05	0.05	0.05	0.06	0.06	0.06	0.06	0.08	0.08
5/8 (15.88)				0.06	0.06	0.06	0.08	0.08	0.10	0.10
18				0.06	0.06	0.08	0.08	0.10	0.10	0.10
3/4 (19.05)					0.07	0.08	0.08	0.10	0.12	0.12

